

Package ‘pbbd’

July 23, 2025

Version 1.0.0

Date 2021-09-06

Title Position Balanced and Nearly Position Balanced Block Designs

Author B N Mandal [aut, cre],
Pramod Katore [aut],
Sukanta Dash [aut],
Rajender Parsad [aut]

Maintainer B N Mandal <mandal.stat@gmail.com>

Depends R (>= 4.1.0)

Imports ibd (>= 1.5)

Description Generates a position balanced or nearly position balanced block design with given parameters. This package can also convert a given proper and equireplicate block design into a position balanced or nearly position balanced block design.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2021-09-08 08:40:02 UTC

Contents

balancify	2
pbbd	3
Index	4

 balancify

Position balanced and nearly position balanced block design

Description

This function generates a position balanced or nearly position balanced block design from a given equireplicate and proper block design

Usage

```
balancify(d1)
```

Arguments

d1 Block design specified in the form of a b x k matrix with elements labelled as 1 to v where b is number of blocks, k is block size and v is number of treatments

Value

design (Nearly) position balanced block design
P Treatment by Position incidence matrix

Note

Input design should be equireplicate that is, each treatment should have equal replications. Block sizes should be same for each block. For any issue, kindly report to author.

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
d1 = matrix(c(3, 4, 6,
5, 6, 7,
1, 4, 5,
2, 4, 7,
1, 3, 7,
1, 2, 6,
2, 3, 5), ncol = 3, byrow = TRUE)
balancify(d1)
```

```
d1 = matrix(c(7, 8, 9,
1, 6, 8,
1, 3, 9,
4, 6, 9,
5, 6, 7,
1, 4, 5,
3, 5, 8,
), ncol = 3, byrow = TRUE)
balancify(d1)
```

```

      3 ,4 ,7 ,
      2 ,5 ,9 ,
      2 ,4 ,8 ,
      1 ,2 ,7 ,
      2 ,3 ,6), ncol = 3, byrow = TRUE)
balancify(d1)

```

pbbd

Position balanced and nearly position balanced block design

Description

This function generates a position balanced or nearly position balanced block design with given parameters. User needs to specify number of treatments (v), number of blocks (b) and block size (k)

Usage

```
pbbd(v, b, k)
```

Arguments

v	Number of treatments
b	Number of blocks
k	Block size

Value

parameters	Parameters v, b, r, k . Here r is number of replications of each treatment
efficiencies	A- and D-efficiency of the design generated
design	Position balanced block design
P	Treatment versus position incidence matrix

Note

This function works for generating a position balanced block design for upto 30 treatments and block size 10. For getting design with larger number of treatments and/or block size, it is better to use `balancify()` function with a design supplied by user to make the design position balanced.

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
pbbd(7, 7, 3)
```

```
pbbd(9, 12, 3)
```

Index

- * **incidence matrix**
 - balancify, 2
 - pbbd, 3
- * **incomplete block design**
 - balancify, 2
 - pbbd, 3
- * **nearly position balanced**
 - balancify, 2
 - pbbd, 3
- * **order balanced**
 - balancify, 2
 - pbbd, 3
- * **position balanced**
 - balancify, 2
 - pbbd, 3

balancify, 2

pbbd, 3